



Transportable Multi-gas area monitor

Detective + A transportable area monitor you can trust

- Loud and bright alarms
- Inherently rugged and reliable
- Wide sensor options including infra-red
- Built-in pump option
- Folding or fixed legs

Used singly or linked together, Detective+ gives a loud and clear alarm providing effective warning of gas hazards. The rugged, water and impact resistant design and clear display make Detective+ the ideal choice for your transportable gas detection needs.

Superb pedigree

- Detective+ is based on the highly successful Triple Plus+ multi-gas monitor which has sold over 55,000 units worldwide

Versatile and user friendly

- Infra-red sensors available
 - allows sampling of potentially high flammable gas levels and CO₂
 - infra-red sensors are unaffected by poisoning
- Built-in pump option provides fast response and extra sensor protection
- Display provides clear information, allows identification of gas hazard
- Easy tracking of multiple hazards
- up to 60 hour battery operation
- Wide range of toxic gas sensors available

Extremely loud and clear alarms

- Wailing omni-directional siren, 104 dBA @1 metre
- High intensity red LED clusters provide visual alarm indication
- All linked Detective+ units indicate an alarm sensed by any one unit
- Units actually sensing alarm have faster LED flash
- Audible and visible confidence blip
- Time weighted average alarms for 8 hours and 15 minutes averages

Uniquely rugged, tripod construction

- Detectors are fully protected, even if device is overturned
- Raised overturners prevent water ingress
- Easy and quick to set up
- Folding or fixed leg options provide easy storage and transportation

Detective +

Specification

Weight	7.5 kg (19lb)		
Dimensions	640 h x 455 w x 455 d mm (25.2 x 17.9 x 17.9 inches)		
Typical measuring ranges and alarm settings (up to four gas measurement channels)		<i>Standard Range</i>	<i>Typical Alarm Levels</i>
	Flammable gas	0 – 100% LEL	20% LEL
	Oxygen	0 – 25%	19% & 23%
	Hydrogen sulphide	0 – 50 ppm	10 ppm
	Carbon monoxide	0 – 500 ppm	35 ppm
	Sulphur dioxide	0 – 10 ppm	2 ppm
	Chlorine	0 – 5 ppm	0.5 ppm
	Nitrogen dioxide	0 – 10 ppm	2 ppm
	Phosphine	0 – 5 ppm	0.5 ppm
	Ammonia	0 – 50 ppm	25 ppm
	Ammonia	0 – 1000 ppm	N/A
	Hydrogen (non-flammable levels)	0 – 2000 ppm	N/A
	Hydrogen cyanide	0 – 25 ppm	10 ppm
	Hydrogen chloride	0 – 10 ppm	5 ppm
	Ozone	0 – 1 ppm	0.3 ppm
	Chlorine Dioxide	0-1ppm	0.1ppm
	Hydrogen Fluoride	0-10ppm	1pm
	Ethylene Oxide	0-10ppm	5ppm
	Volatile Organic	0-100ppm	N/A
Infrared Sensors	Infrared sensors for flammable gas can be supplied as a single range, 0-100% LEL, utilising a single display channel, or as a dual range, 0-100% LEL/0-100% volume, which then occupies two display channels. CO ₂ sensors are supplied as 0-2% volume. Only one IR sensor can be fitted, and IR sensors can only be used in combination with oxygen and toxic sensors		
		<i>Standard Range</i>	<i>Alarm</i>
	Flammable Gas	0-100% LEL	20% LEL
	Flammable Gas	0-100% v/v	None
	Flammable Gas	available for methane, propane, butane or ethylene	
	CO ₂	0-2.0% v/v	0.5/1.5% v/v
Typical response times	Methane 20 s, Oxygen 10 s, typical toxic gas 20 s, IR 30 s		
Expected sensor life	Flammable 5 years, Toxic 3 years, Oxygen 2 year minimum, IR >5 years		
Audible alarms	Wailing, omni-directional siren, 104 dBA @ 1 metre.		
Visible alarms	Three large, top-mounted red LED clusters and single red LED on control panel. In alarm mode LED clusters flash in quick succession LED clusters of linked Detectives repeating the alarm, flash more slowly than LED lights on those Detectives sensing the hazard. Slow flashing green LED indicates normal working. Rapid flashing green LED indicates low battery.		
Display	High contrast LCD with back light 2 lines of 24 characters. Values and units for up to 4 gases displayed simultaneously at current, TWA or peak levels. Low battery, real time and elapsed time, calibration and configuration data also displayed		

Datalogging	Adjustable sample rate, 100 hours @ 1 minute sample rate (maximum 6000 data points per channel) Logging of events, user and site data
Menu	Operating menu allows access to setting up of instrument operation Log Menu allows selection of Users and Sites from predefined lists, marking the log file with an event, and start or stop of data logging Configuration Menu allows selection of display and alarm modes, setting of alarms, zero and calibration, and selection of flammable gas correction factors from predefined list .
Battery	6 V, 7.2 Ah Sealed lead acid battery pack Optional 6V, 12Ah high capacity pack
Battery life	Standard instrument: Up to 36 hours assuming flammable/CO ₂ sensor fitted with 7.2Ah battery. Up to 60 hours with optional 12Ah battery pack
Battery charging	Built-in battery charging circuit, dual rate 100 – 120 VAC and 200 - 250 V AC Input options available. (Safe Area operation only) Typical charge time: 12 hours
Operating Temperature range	-20°C to +40°C (-4°F to 104°F).
Humidity	0 – 95% RH non condensing
Approvals	Europe : ATEX II 2G EEx ib d IIC T4 USA and Canada : Class 1 Division 1 Groups A, B, C, D (Pending)
Standards	EN50014, EN50020, 94/9/EC UL913 and CSA 22.2
Ingress protection	IP65
EMC	EN 50270
PC Interface	Detective+ has an in-built PC interface, which can be connected to the serial port of a computer using the optional RS232 lead. Portables PC software can be used to set alarms, clock, datalogging interval and password. Portables PC also controls datalogging, giving graphical display of instrument log file and allows file export to spreadsheet.
Calibration	Detective+ can be routinely calibrated quickly using its internal menu command, Portables PC or the Crowcon CheckBox IMH management system
Accessories	Baffle plate (to protect sensors) Interconnecting lead - 10 m standard, longer lengths up to 100m available Computer lead - RS232 serial link Portables PC software Aspirator Manual bulb and 2 m hose, both non-absorbent and hydrocarbon resistant Internal electric sampling pump option includes external water trap and 2m hose, longer lengths available on request
Linked Detectives	Up to 12 units can be linked to provide perimeter or area monitoring



UK Office
Crowcon Detection Instruments Ltd
2 Blacklands Way
Abingdon Business Park
Abingdon
Oxfordshire OX14 1DY
United Kingdom
Tel: +44 (0) 1235 557700
Fax: +44 (0) 1235 557749
Email: crowcon@crowcon.com
Web Site: www.crowcon.com

USA Office
Crowcon Detection Instruments Ltd
21 Kenton Lands Road
Erlanger
Kentucky 41018-1845
USA
Tel: +1 859 957 1039 or
1-800-5-CROWCON
Fax: +1 859 957 1044
Email: sales@crowconusa.com
Web Site: www.crowcon.com

Rotterdam Office
Crowcon Detection Instruments Ltd
Vlambloem 129
3068JG, Rotterdam
Netherlands
Tel: +31 10 421 1232
Fax: +31 10 421 0542
Email: crowcon@crowcon.net
Web Site: www.crowcon.net

Singapore Office
Crowcon Detection Instruments Ltd
Block 192 Pandan Loop
#05-01 Pantech Industrial Complex
Singapore 128381
Tel: +65 6745 2936
Fax: +65 6745 0467
Email: sales@crowcon.com.sg
Web Site: www.crowcon.com

PO1025 Issue 1 01/06