


# PYROVIEW Accessories

## I/O box

Part number: 2301A04010



### Description

For the use of the internal camera inputs or camera outputs an I/O box is available. This box contains besides the power supply of the camera and clamping units for the system cable also clamping units for the camera inputs and relays for the camera outputs.

A RJ45 coupler for the Ethernet connector of the camera is available. The I/O box is versatile upgradeable and individually configurable. An addition for the operation of a second camera (2301A04011) in combination with a Gigabit Ethernet switch (2301409220) is possible.

For cable lengths greater than 100 m a media converter Ethernet → Fiber optics cable (2301A09315) can be used. Additional inputs and outputs are available by means of pre-configured WAGO systems.

All incoming cables can be easily installed by a cable gland system and are thereby protected.

### Technical data

Providing the supply voltage	direct-current voltage 24 V DC
Camera connection	clamping units for the system cable of the camera RJ45 coupler for Ethernet cable of the camera 2 relays for camera outputs
Dimensions	400 mm × 300 mm × 120 mm (W × H × D)
Weight	approx. 3 kg (depending on configuration)
Power supply	230 V AC, typical 20 V A
Housing	powder coated steel sheet, IP65
Installation	install the box with the help of the mounting links
Allowed operating temperature	0 °C to 50 °C
Storage conditions	-20 °C to 70 °C, max. 95 % relative humidity
Power pack	cap rail power pack 100-240 V AC, 47-63 HZ, 24 V DC 1A

# PYROVIEW Accessories

## I/O box

Accessories	
Description	Part number
System cable for PYROVIEW compact+, HC10, 12 pin, wire ends are open	
System cable 5 m	2301A14006
System cable 10m	2301A14011
System cable 20 m	2301A14021
System cable 25 m	2301A14026
System cable 30 m	2301A14022
Ethernet cable for PYROVIEW compact+, (M12-RJ45, Cross, 8 pin)	
Ethernet cable 5 m	2301A32005
Ethernet cable 10 m	2301A32010
Ethernet cable 15 m	2301A32015
Ethernet cable 20 m	2301A32020
Ethernet cable 25 m	2301A32025
Ethernet cable 30 m	2301A32030
System cable for PYROVIEW protection, RC16, 16 pin, wire ends are open	
System cable 5 m	2301A12005
System cable 10 m	2301A12010
System cable 20 m	2301A12020
System cable 25 m	2301A12025
System cable 30 m	2301A12030
System cable 20 m , high-temperature (7 pin) temperature range: -20 °C ... 125 °C	2301A12020HT
Ethernet cable for PYROVIEW protection, Ethernet cable (M12-RJ45, Cross, 8 pin)	
Ethernet cable 5 m	2301A32005
Ethernet cable 10 m	2301A32010
Ethernet cable 15 m	2301A32015
Ethernet cable 20 m	2301A32020
Ethernet cable 25 m	2301A32025
Ethernet cable 30 m	2301A32030
Ethernet cable 20 m high-temperature, temperature range: -20 °C ... 125 °C	2301A32020HT
Miscellaneous	
Add-on for the connection of a second camera	2301A04011
Gigabit Ethernet switch	2301409220
Media converter (Ethernet → Fiber optics cable)	2301A09315
WAGO controller, IO: WAGO 8 DO /8 AO/2 DI	2301A09115
WAGO controller, IO: WAGO 4 DO/4 AO/2 DI	2301A09116
WAGO controller, IO: WAGO 8 DO/2 DI	2301A09117
WAGO controller, IO: zone data output module	2301A09118
WAGO controller, IO: customized	on request

Technische Änderungen vorbehalten. Technical details are subject to change. 23.11.16



We are certified for many years according to ISO 9001

**DELTA STRUMENTI S.r.l**  
 Via Mattei 6 - 21036 GEMONIO (VA)  
 Tel 0332 604.667 - Fax 0332 610.511  
 info@deltastrumenti.it - www.deltastrumenti.it

