

Hipot Safety Analyser

S 6700H, S 6700U, KT 6780H

Whatever electrical safety test you need to carry out, with a Hipot Safety Analyser you will always make the right choice.

Our safety tester combine up to 7 test types in one compact device - from high-voltage testing, insulation testing and ground bond testing to functional testing. Our devices for testing electrical safety enable tests in accordance with all common standards (VDE, EN, IEC, etc.).

The products impress with a wide range of technical features:

- Numerous interfaces
- Automatic test sequence
- Fully electronic generator (for even faster and more accurate tests) and many other features



Hipot Safety Analyser

S 6700H, S 6700U, KT 6780H

		S 6700H	S 6700U	KT 6780H
		Desktop device	Desktop device	Rack device
High Voltage Test AC	Voltage Range Current Range Short Circuit Current		100 V - 5500 V 0 mA - 20 mA >20 mA	
High Voltage Test DC	Voltage Range Current Range Short Circuit Current Residual Ripple		100 V - 6000 V 0 mA - 20 mA >20 mA < 3%	
Insulation Measurement DC	Voltage Range Measuring Range Residual Ripple		100 V - 6000 V 100 k Ω - 50 G Ω < 3%	
Ground Bond Test	Test Current AC Measuring Range Open Circuit Voltage		1 A - 32 A 1 m Ω - 6 Ω 6 V	
Equivalent Leakage Current Test	Test Voltage AC Measuring Range		90 V - 270 V 0 mA - 10 mA	
Resistance Measurement	Measuring Range		1 Ω - 1 M Ω	
Continuity Test	Measuring Range		<14 Ω \triangle short circuit i > 100 k Ω \triangle no continuity	
Measured Variables in Function Test	Current AC / DC Voltage AC / DC Active Power ReActive Power Apparent Power Cos Φ		16 A AC / 10 A DC 250 V AC / 200 V DC 0 W - 4000 W 0 - 4000 var 0 VA - 4000 VA -1 - +1	
Digital Interface 24 VDC	Input Output		4 4	
Mains Supply	Voltage Frequency		90 V - 250 V 50 Hz / 60 Hz	
Interfaces	Computer Interfaces Ethernet / LAN		USB \checkmark	
Operation	Touch for Input		7"-TFT colour display	
Dimensions and Weight (approx.)	Height Width Depth Weight		148 mm 5.8 in 420 mm 16.5 in 508 mm 20.0 in 20,4 kg 45.0 lbs	133 mm 5.2 in 482 mm 19.0 in 439 mm 17.3 in 20,4 kg 45.0 lbs