

Hipot Tester

HA 1885B

The HA 1885B hipot tester combines High Voltage testing (AC and DC) and insulation testing in a single device. The HA 1885B is ideal for fast, cost-effective and convenient safety testing in accordance with current national and international standards (IEC, EN, UL, VDE etc.).

The standard integrated 10.1" touch color display ensures maximum convenience and ease of use. Simple and clear instructions on the display make operation intuitive and efficient.

Thanks to the individually configurable test programs, a fully automatic test plan can also be created for each product. With a short-circuit current of 3 mAAC / 10 mADC, the HA 1885B tester is safety current-limited (in accordance with EN 50191) and makes it easier to set up a safe workplace.

This means that it can be used by non-qualified electricians. The HA 1885B also has a fully electronic High Voltage generator, which ensures accurate and fast testing.



Hipot Tester

HA 1885B

		HA 1885B
		Desktop device
High Voltage Test AC	Voltage Range Current Range Short Circuit Current	100 V - 5500 V 0 mA - 3 mA < 3 mA
High Voltage Test DC	Voltage Range Current Range Short Circuit Current Residual Ripple	100 V - 6000 V 0 mA - 10 mA < 12 mA < 3 %
Insulation Measurement DC	Voltage Range Measuring Range (voltage-dependent) Residual Ripple	100 V - 6000 V 250 k Ω - 6 G Ω < 3 %
ARC Detection (opt.)	Range	0 % - 100 %
Subjective Tests	Picture-Step / Text-Step	Subjective or informative
General Data	Threshold Values Error Message Clock / Calendar Ramp Function Generator Memory Additional Function Mains Supply	All programmable Visual and audible Internal Programmable Fully electronic, digital technology Up to 64 GB Programmable inputs and outputs 90 V - 250 V 50 Hz / 60 Hz
Interfaces	Computer Interfaces Digital Interface 24 VDC Analogue Interfaces 10 VDC	USB, RS 232, Ethernet / LAN, CAN 8 input + 8 output 2 x input + 1 x output
Operation	Touch for Input	10.1"-TFT colour display
Dimensions and Weight (approx.)	Height Width Depth Weight	222 mm 8.7 in 483 mm 19.0 in 491 mm 19.3 in 18 kg 39.7 lbs