

Wind Direction Transmitter Classic

Potentiometer-wind-direction-transmitters are equipped with a sliding potentiometer which offers a theoretically unlimited resolution.

The heating is electronically controlled. A plug-connection is situated in the shaft of the instrument. The instrument is mounted preferably onto a mast or traverse. All main parts are made of anodised aluminium.

Specification

Part number: 4.3120.22.xxx

Wind direction

Measuring range	0 ... 360 °
Resolution	1 °
Accuracy	see models
Starting value	0.5 m/s at 90 °
Damping ration	> 0.3 acc. to ASTM D 5096-96

Data output analog

Wind direction	see models
----------------	------------

Operating voltage

Potent. / Elektronik	0 ... 12 V DC, max 1.5 W
Heating	24 V AC/DC, 20 W

General

Ambient temp.	-35 ... +80 °C
Electr. connection	8 pol. plug connection
Mounting	onto mast tube Ø 1,5 ``
Protection	IP 55
Dimension	Ø 850 x 415 mm
Survival speed	60 m/s
Weight	1.8 kg
Mounting	Ø 50 x 50 mm

Versions

As per 4.3120.22.xxx, but:

Product number 4.3120.22.012

Wind direction

Measuring range	0 ... 360 °
Accuracy	±2 °

Data output analog

Wind direction	0 ... 2 k
----------------	-----------

Operating voltage

Potent. / Elektronik	Current limiting to max. 1 mA
----------------------	-------------------------------

Product number 4.3120.22.018

Wind direction

Measuring range 0 ... 358 °

Accuracy ±3 °

Data output analog

Wind direction 0 ... 400

Accessories

No accessories are available for this product.

